

 ICOM

VHF MARINE TRANSCEIVER

IC-M25EURO

Buoyant, Stylish and Easy to Use



● Marine Blue



Jacobs
www.jbe.nl



● Metallic Gray

● Pearl White



**Slim, Lightweight,
High Performance**



**USB Charging
(Micro-B USB type)**



**11 Hours
of Battery Life**



**Large LCD,
Simple User Interface**



Float'n Flash



**Optional Speaker-
Microphone, HM-213**



Float'n Flash image

*For illustration purpose only

FEATURES

Slim, Lightweight, High Performance

The IC-M25EURO has the slimmest (depth: 30.5mm) and lightest (220g) body as a floating marine transceiver*. It also delivers uncompromised performance that will exceed expectations.

*As of July, 2015, researched by Icom.

Large LCD, Simple User Interface

The IC-M25EURO's LCD is 30% larger than its predecessor, the IC-M23 and shows clearly large channel number and status icons. The buttons on the front panel are well laid out and provide simple and straightforward operation.

USB Charging (Micro-B USB type)

A standard USB connector (Micro-B type) is used for charging the IC-M25EURO. Cigarette lighter cables or mobile batteries for charging smartphones or other devices can be used with the IC-M25EURO*.


* The IC-M25EURO accepts 5V/1A (Max.) input. Use of third-party products is not guaranteed.

Float'n Flash

The IC-M25EURO floats and lets you know where it is with the flashing red LED light and LCD/key backlight.

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.



SPECIFICATIONS

GENERAL		
Frequency range	Tx Rx	156.000-161.450MHz 156.000-163.425MHz
	HOL version Tx Rx	156.000-161.600MHz 156.000-163.425MHz
Usable channel groups		INT, USA*, ATIS*channels * Depending on version
Type of emission		16K0G3E (FM)
Power supply voltage		3.7V DC nominal
Current drain (at 3.7V DC)	Tx Rx (Internal SP/External SP)	2.3A 300mA/200mA (Max. audio)
Operating temperature range		-15°C to +55°C
Antenna impedance		50Ω
Dimensions (W×H×D) (projections not included)		56.6×134.2×30.5mm
Weight (approximately)		220g (With FA-SC59V and MB-133)
TRANSMITTER		
Output power		5W(approx.)/1W/0.5W* * For only FRG version
Max. frequency deviation		±5.0kHz
Frequency stability		±1.5kHz
Spurious emissions		0.25μW
Adjacent channel power		70dB
Residual modulation		40dB
RECEIVER		
Sensitivity		-6dBμ emf typ. (at 20dB SINAD)
Squelch sensitivity		-6dBμ emf typ. (at threshold)
Adjacent channel selectivity		70dB
Spurious response		70dB
Intermodulation		68dB
Audio output power (at 10% distortion)	Internal SP External SP	550mW typ. (12Ω load, at 1 kHz) 200mW (4Ω load)
Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.		
Applicable IP Rating		
Ingress Protection Standard		
Water		IPX7 (Waterproof protection)

11 Hours of Battery Life

The built-in 1500mAh lithium-ion battery allows 11 hours (approx.) of long operation*.

* Typical operation with Tx (HI): Rx: standby=5:5:90

Optional Speaker-Microphone, HM-213

The optional waterproof speaker-microphone, HM-213, provides commercial grade convenience while mounting the radio around the waist. The radio floats even when the HM-213 is attached.

550mW Audio Output

The IC-M25EURO provides a powerful 550mW (typical) audio output and received voice can be heard loud and clear.

Other Features

- IPX7 waterproof construction (1m depth of water for 30 minutes)
 - 4-step battery life indicator
 - Dual/Tri-watch functions*
 - Instant access to Ch 16 or programmable call channel
 - Favorite channel function
 - Monitor function opens noise squelch
 - Auto scan function*
 - LCD auto backlighting
 - AquaQuake™ draining function
- * Except HOL version

Supplied accessories:



The "3D GENUINE Icom label" is attached to the rear panel. Check the Icom website for details: <http://www.icom.co.jp/world/genuine-info/>

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

Icom Inc.

1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom Canada

Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Brazil

Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (Europe) GmbH

Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-0
E-mail: info@icom-europe.com
URL: <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom (UK) Ltd.

Blacksole House, Altira Park,

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejone des Moulinas, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom New Zealand

39C Rennie Drive, Airport Oaks,

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

